NSN 5930-01-296-2218

Push Switch - Page 1 of 2

Horizontal split lens; positive indexing



view Online at https://aerobasegroup.com/hsh/5930-01-296-2216
Body Style:
Panel mount
Hazardous Locations/environmental Protection:
Moisture resistant
Overall Length:
1.210 inches
Overall Height:
3.320 inches
Overall Width:
Between 0.950 inches and 0.970 inches
Body Length:
0.660 inches
Body Width:
Between 0.950 inches and 0.970 inches
Body Height:
3.110 inches
Case Material:
Metal
Actuator Length:
Between 1.020 inches and 1.050 inches
Actuator Style:
Rectangular
Actuator Height:
Between 0.164 inches and 0.210 inches
Actuator Width:
Between 0.720 inches and 0.750 inches
Actuator Color:
White single actuator and white single actuator
Illuminated Actuator Color:
Green single actuator and green single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Nonpile-up Contact Arrangement:
2 pole, double throw, both positions maintained single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac
Special Features:

NSN 5930-01-296-2218

Push Switch - Page 2 of 2



Precious Material And Location:
Contacts silver
Terminal Type And Quantity:
6 turret and 5 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A053a0