

View Online at <https://aerobasegroup.com/nsn/5930-01-296-3524>

Thread Class:

2a

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Humidity resistant and salt spray resistant and shock resistant and vibration resistant

Overall Length:

2.513 inches

Overall Height:

Between 0.860 inches and 0.895 inches

Overall Width:

Between 0.860 inches and 0.895 inches

Body Diameter:

Between 0.860 inches and 0.890 inches

Bushing Length:

Between 0.855 inches and 0.895 inches

Body Length:

0.468 inches

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.750 inches

Contact Load Current Rating At Maximum Rated Voltage:

200.000 milliamperes resistive dc and 30.000 milliamperes inductive dc and 100.000 milliamperes lamp dc and 150.000 milliamperes resistive ac

Special Features:

Switch has a unique key and tumbler system

Precious Material And Location:

Terminal surfaces gold and c0ntacts silver

Thread Series Designator:

Uns

Terminal Type And Quantity:

1 turret and 6 tab, solder lug

Specification Data:

76301-70b184109 manufacturers source control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0