

View Online at <https://aerobasegroup.com/nsn/5930-01-296-3524>

**Thread Class:**

2a

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Humidity resistant and salt spray resistant and shock resistant and vibration resistant

**Overall Length:**

2.513 inches

**Overall Height:**

Between 0.860 inches and 0.895 inches

**Overall Width:**

Between 0.860 inches and 0.895 inches

**Body Diameter:**

Between 0.860 inches and 0.890 inches

**Bushing Length:**

Between 0.855 inches and 0.895 inches

**Body Length:**

0.468 inches

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.750 inches

**Contact Load Current Rating At Maximum Rated Voltage:**

200.000 milliamperes resistive dc and 30.000 milliamperes inductive dc and 100.000 milliamperes lamp dc and 150.000 milliamperes resistive ac

**Special Features:**

Switch has a unique key and tumbler system

**Precious Material And Location:**

Terminal surfaces gold and c0ntacts silver

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

1 turret and 6 tab, solder lug

**Specification Data:**

76301-70b184109 manufacturers source control

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0