

View Online at <https://aerobasegroup.com/nsn/5930-01-296-6747>

**Body Style:**

Bushing mount

**Overall Length:**

Between 1.110 inches and 1.140 inches

**Overall Height:**

Between 1.174 inches and 1.264 inches

**Overall Width:**

Between 0.610 inches and 0.640 inches

**Bushing Length:**

Between 0.453 inches and 0.483 inches

**Body Length:**

Between 1.110 inches and 1.140 inches

**Body Width:**

Between 0.610 inches and 0.640 inches

**Body Height:**

Between 0.610 inches and 0.640 inches

**Actuator Style:**

Round

**Actuator Diameter:**

Between 0.237 inches and 0.243 inches

**Actuator Height:**

Between 0.673 inches and 0.703 inches

**Actuator Position-action Relationship:**

Up position momentary and down position momentary and center position maintained

**Maximum Voltage Rating In Volts:**

250.0 ac and 250.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, two positions momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

10.000 amperes resistive dc and 10.000 amperes resistive ac

**Precious Material And Location:**

Terminal surfaces silver

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

3 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0