

View Online at <https://aerobasegroup.com/nsn/5930-01-296-6747>

Body Style:

Bushing mount

Overall Length:

Between 1.110 inches and 1.140 inches

Overall Height:

Between 1.174 inches and 1.264 inches

Overall Width:

Between 0.610 inches and 0.640 inches

Bushing Length:

Between 0.453 inches and 0.483 inches

Body Length:

Between 1.110 inches and 1.140 inches

Body Width:

Between 0.610 inches and 0.640 inches

Body Height:

Between 0.610 inches and 0.640 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.237 inches and 0.243 inches

Actuator Height:

Between 0.673 inches and 0.703 inches

Actuator Position-action Relationship:

Up position momentary and down position momentary and center position maintained

Maximum Voltage Rating In Volts:

250.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, two positions momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 10.000 amperes resistive ac

Precious Material And Location:

Terminal surfaces silver

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0