

View Online at <https://aerobasegroup.com/nsn/5930-01-296-7558>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Corrosion resistant

Overall Length:

0.510 inches

Overall Height:

1.187 inches

Overall Width:

0.575 inches

Bushing Length:

Between 0.260 inches and 0.270 inches

Body Length:

0.510 inches

Body Width:

0.465 inches

Body Height:

0.435 inches

Actuator Style:

Round

Actuator Diameter:

0.105 inches

Actuator Height:

Between 0.257 inches and 0.287 inches

Actuator Position-action Relationship:

Up position maintained and down position momentary and center position maintained

Maximum Voltage Rating In Volts:

28.0 dc

End Application:

5820-01-223-8487 converter, signal da

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

500.000 milliamperes resistive dc and 500.000 milliamperes inductive dc and 500.000 milliamperes lamp dc

Special Features:

Non threaded bushing terminal mounted

Precious Material And Location:

Terminal surfaces gold or terminal surfaces silver

Test Data Document:

81349-mil-s-83731 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

6 printed circuit

Specification Data:

81349-mil-s-83731/16 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0