

View Online at <https://aerobasegroup.com/nsn/5930-01-296-7558>

**Body Style:**

Bushing mount

**Hazardous Locations/environmental Protection:**

Corrosion resistant

**Overall Length:**

0.510 inches

**Overall Height:**

1.187 inches

**Overall Width:**

0.575 inches

**Bushing Length:**

Between 0.260 inches and 0.270 inches

**Body Length:**

0.510 inches

**Body Width:**

0.465 inches

**Body Height:**

0.435 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.105 inches

**Actuator Height:**

Between 0.257 inches and 0.287 inches

**Actuator Position-action Relationship:**

Up position maintained and down position momentary and center position maintained

**Maximum Voltage Rating In Volts:**

28.0 dc

**End Application:**

5820-01-223-8487 converter, signal da

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Features Provided:**

Actuator seal

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

500.000 milliamperes resistive dc and 500.000 milliamperes inductive dc and 500.000 milliamperes lamp dc

**Special Features:**

Non threaded bushing terminal mounted

**Precious Material And Location:**

Terminal surfaces gold or terminal surfaces silver

**Test Data Document:**

81349-mil-s-83731 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

6 printed circuit

**Specification Data:**

81349-mil-s-83731/16 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0