NSN 5930-01-297-3199

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-297-3199

Body Style:
Hole mounted
Actuator Length:
1.375 inches
Actuator Style:
Roller arm
Actuator Height:
0.555 inches
Actuator Roller Diameter:
0.750 inches
Actuator Roller Width:
0.250 inches
Housing Height:
1.750 inches
Housing Length:
4.230 inches
Housing Width:
1.605 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
2.344 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:
1.156 inches
Maximum Voltage Rating In Volts:
600.0 ac and 250.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded hole
Thread Size:
0.190 inches
Nonpile-up Contact Arrangement:
1 two circuit, one position momentary single switch unit
Switch Actuating Force:
50.0 inch-ounces
Actuator Movement:
11.0 pretravel degrees and 64.0 overtravel degrees and 5.0 differential degrees
Contact Load Current Rating At Maximum Rated Voltage:
0.270 amperes resistive dc and 1.200 amperes resistive ac

Unf

Terminal Type And Quantity:

Thread Series Designator:

4 screw

NSN 5930-01-297-3199

Sensitive Switch - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0