

View Online at <https://aerobasegroup.com/nsn/5930-01-297-5951>

**Thread Class:**

2b single mounting facility

**Hazardous Locations/environmental Protection:**

Moisture resistant

**Overall Length:**

0.375 inches

**Overall Height:**

1.645 inches

**Overall Width:**

1.700 inches

**Distance Between Mounting Facility Centers:**

1.437 inches single mounting facility

**Individual Section Quantity:**

1

**End Application:**

4920-01-230-5964 test set, engine operation

**Mounting Method:**

Flange single mounting facility and threaded hole single mounting facility

**Actuator Type:**

Double push button all actuators

**Thready Qty Per Inch (tpi):**

56 single mounting facility

**Thread Size:**

0.086 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Mounting Facility Pattern:**

Two position in-line single mounting facility

**Switch Actuator Indexing Position Quantity:**

12 all actuators

**Terminal Type:**

Printed circuit

**Contact Load Current Rating:**

125.0 milliamperes resistive load dc at sea level

**Readout Indicator Marking:**

0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11 single section

**Contact Arrangement Truth Table:**

Binary code, 1 pole - 12 positions single section

**Special Features:**

Panel seal

**Color:**

Black single body

**Style Designator:**

Rectangular indicating

**Thread Series Designator:**

Unc single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0