

View Online at <https://aerobasegroup.com/nsn/5930-01-297-5951>

Thread Class:

2b single mounting facility

Hazardous Locations/environmental Protection:

Moisture resistant

Overall Length:

0.375 inches

Overall Height:

1.645 inches

Overall Width:

1.700 inches

Distance Between Mounting Facility Centers:

1.437 inches single mounting facility

Individual Section Quantity:

1

End Application:

4920-01-230-5964 test set, engine operation

Mounting Method:

Flange single mounting facility and threaded hole single mounting facility

Actuator Type:

Double push button all actuators

Thready Qty Per Inch (tpi):

56 single mounting facility

Thread Size:

0.086 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Mounting Facility Pattern:

Two position in-line single mounting facility

Switch Actuator Indexing Position Quantity:

12 all actuators

Terminal Type:

Printed circuit

Contact Load Current Rating:

125.0 milliamperes resistive load dc at sea level

Readout Indicator Marking:

0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11 single section

Contact Arrangement Truth Table:

Binary code, 1 pole - 12 positions single section

Special Features:

Panel seal

Color:

Black single body

Style Designator:

Rectangular indicating

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0