

View Online at <https://aerobasegroup.com/nsn/5930-01-297-5952>

Body Style:

Hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.998 inches and 1.002 inches

Overall Height:

1.562 inches

Overall Width:

Between 0.675 inches and 0.705 inches

Body Length:

Between 1.925 inches and 1.955 inches

Body Width:

Between 0.675 inches and 0.705 inches

Body Height:

Between 0.770 inches and 0.830 inches

Unthreaded Mounting Hole Diameter:

Between 0.139 inches and 0.143 inches

Actuator Length:

Between 1.828 inches and 1.892 inches

Actuator Style:

Roller arm

Actuator Free Position Height:

1.187 inches

Actuator Roller Diameter:

Between 0.355 inches and 0.385 inches

Actuator Roller Width:

Between 0.145 inches and 0.175 inches

Maximum Voltage Rating In Volts:

480.0 ac and 250.0 dc

End Application:

Mb-4 aircraft towing tractor

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Features Provided:

Actuator seal

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

0.75 ounces

Switch Actuating Force:

Between 1.0 ounces and 3.5 ounces

Actuator Movement:

0.094 pretravel inches

Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 20.000 amperes resistive ac

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0