

View Online at <https://aerobasegroup.com/nsn/5930-01-297-6738>

Thread Class:

2a

Body Style:

Bushing mounted

Body Diameter:

1.000 inches

Bushing Length:

1.000 inches

Body Length:

1.165 inches

Actuator Style:

Round

Actuator Diameter:

0.250 inches

Actuator Height:

0.380 inches

Actuator Free Position Height:

1.380 inches

Maximum Voltage Rating In Volts:

28.0 dc

End Application:

1410-01-267-6685 guided missile

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thread Size:

0.625 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Switch Release Force:

64.0 ounces

Switch Actuating Force:

Between 96.0 ounces and 192.0 ounces

Actuator Movement:

Between 0.040 pretravel inches and 0.250 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc

Thread Series Designator:

Unef

Terminal Type And Quantity:

4 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A053a0