NSN 5930-01-297-9808

Code Indicating Wheel Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-297-9808

Hazardous Locations/environmental Protection:

Shock resistant and vibration resistant

Overall Length:

1.415 inches

Overall Height:

2.294 inches

Overall Width:

1.875 inches

Unthreaded Mounting Hole Diameter:

0.140 inches single mounting facility

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

1.080 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

1.565 inches single mounting facility

Operating Tempurature Range:

-65.0/+85.0 degrees celsius

Mounting Method:

Bracket single mounting facility and unthreaded hole single mounting facility

Actuator Type:

Thumbwheel single actuator

Contact Voltage Rating In Volts:

28.0 ac at sea level28.0 dc at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

8 single actuator

Terminal Type:

Printed circuit

Contact Load Current Rating:

125.0 milliamperes resistive load ac at sea level125.0 milliamperes resistive load dc at sea level

Readout Indicator Marking:

0, 1, 2, 3, 4, 5, 6, 7 single section

Contact Arrangement Truth Table:

Bcd complement only, 1 pole - 8 positions single section

Color:

Black single bodyblack single indicator backgroundwhite single indicator marking

Style Designator:

Rectangular inline indicating

Shelf Life:

N/a

NSN 5930-01-297-9808

Code Indicating Wheel Switch - Page 2 of 2



| ш | ın | 10 | <i>(</i>)+ | Measure: | |
|---|----|----|-------------|----------|--|
| | | | | | |

--

Demilitarization:

No

Fiig:

A052b0