NSN 5930-01-298-3449

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-298-3449

Overall Length:
2.156 inches
Overall Height:
4.406 inches
Overall Width:
1.812 inches
Mounting Slot Width:
0.142 inches
Capillary Tube Length:
96.0 inches
Bulb Length:
2.500 inches
Bulb Diameter:
0.290 inches
Longest Horizontal Distance Between Mounting Centers:
1.562 inches
Longest Vertical Distance Between Mounting Centers:
2.938 inches
Tempurature Sensing Element Type:
Capillary tube-bulb
Operating Tempurature Rating:
Between -30.0 degrees fahrenheit and 550.0 degrees fahrenheit
Mounting Method:
Bracket and slot
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Four position rectangular
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Screw
Contact Load Current Rating:
9.2 amperes motor load second voltage
Contact Adjustability:
Actuation point adjustable, preset
Contact Adjustment Range:
+70.00/+200.00 actuation point degrees fahrenheit
Contact Adjustment Type:
External actuation point knob with scale

Contact Stimulus Rating:

135.00 actuation point degrees fahrenheit

NSN 5930-01-298-3449

Thermostatic Switch - Page 2 of 2



Contact Voltage Rating In Volts:
240.0 ac at sea level third voltage
Media For Which Designed:
Gas or liquid
Style Designator:
Rectangular
Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0