## NSN 5930-01-298-3450

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-298-3450

	lala		/ · -!	F	Protection:
п	iazardous	Locations	/environiii	entai F	rotection:

Vibration resistant

**Overall Length:** 

Between 1.160 inches and 1.260 inches

**Overall Height:** 

0.526 inches

**Body Diameter:** 

0.460 inches

**Mounting Slot Width:** 

Between 0.133 inches and 0.147 inches

**Body Height:** 

Between 0.280 inches and 0.395 inches

**Unthreaded Mounting Hole Diameter:** 

Between 0.133 inches and 0.147 inches

**Distance Between Mounting Facility Centers:** 

Between 0.930 inches and 0.944 inches

**Tempurature Sensing Element Type:** 

Internal sensor

**Operating Tempurature Rating:** 

Between -65.0 degrees fahrenheit and 500.0 degrees fahrenheit

**Mounting Method:** 

Bracket and slot and unthreaded hole

Features Provided:

Hermetically sealed case

**Contact Action Stimulus:** 

Increase

**Mounting Facility Pattern:** 

Two position in-line

**Nonpile-up Contact Arrangement:** 

1 pole, single throw, normally open, momentary action

**Terminal Type:** 

Tab, solder lug

**Contact Load Current Rating:** 

5.0 amperes resistive load second voltage and 2.5 amperes inductive load second voltage and 1.5 amperes lamp load second voltage

**Contact Adjustability:** 

Actuation point not adjustable and deactuation point not adjustable

**Contact Stimulus Rating:** 

125.00 actuation point degrees fahrenheit and 115.00 deactuation point degrees fahrenheit

**Contact Voltage Rating In Volts:** 

28.0 dc at sea level second voltage

Frequency In Hertz:

60.0 first voltage

## NSN 5930-01-298-3450

Thermostatic Switch - Page 2 of 2

A048b0



Media For Which Designed:
Gas or liquid
Style Designator:
Disc w/flange
Test Data Document:
81349-mil-s-24236 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-s-24236/1 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: