

View Online at <https://aerobasegroup.com/nsn/5930-01-298-5064>

**Body Style:**

Panel mount

**Hazardous Locations/environmental Protection:**

Shock proof

**Overall Length:**

Between 0.730 inches and 0.770 inches

**Overall Height:**

1.914 inches

**Overall Width:**

Between 0.730 inches and 0.770 inches

**Body Length:**

0.695 inches

**Body Width:**

0.695 inches

**Body Height:**

1.729 inches

**Case Material:**

Metal

**Actuator Length:**

Between 0.530 inches and 0.570 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

0.185 inches

**Actuator Width:**

Between 0.530 inches and 0.570 inches

**Actuator Color:**

Black single actuator and black single actuator

**Illuminated Actuator Color:**

Green single actuator and yellow single actuator

**Actuator Inscription:**

Stby oper single actuator

**Illuminated Actuator Color Sequence:**

Upper half of actuator yellow lower half of actuator green

**Maximum Voltage Rating In Volts:**

28.0 dc

**End Application:**

Receiver set, infrared warning an/aar-44

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Nonpile-up Contact Arrangement:**

2 pole, double throw, double break/double make, permanent jumper, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

1.000 amperes resistive dc and 0.500 amperes inductive dc

**Special Features:**

Horizontal split lens

**Precious Material And Location:**

Contacts gold

**Terminal Type And Quantity:**

13 pin

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0