

View Online at <https://aerobasegroup.com/nsn/5930-01-298-5978>

Body Style:

Panel mount

Hazardous Locations/environmental Protection:

Shock proof

Overall Length:

Between 0.730 inches and 0.770 inches

Overall Height:

1.914 inches

Overall Width:

Between 0.730 inches and 0.770 inches

Body Length:

0.695 inches

Body Width:

0.695 inches

Body Height:

1.729 inches

Case Material:

Metal

Actuator Length:

Between 0.530 inches and 0.570 inches

Actuator Style:

Rectangular

Actuator Height:

0.185 inches

Actuator Width:

Between 0.530 inches and 0.570 inches

Actuator Color:

Black single actuator and black single actuator

Illuminated Actuator Color:

Green single actuator and red single actuator

Actuator Inscription:

Power cryo single actuator

Illuminated Actuator Color Sequence:

Upper half of actuator green lower half of actuator yellow

Maximum Voltage Rating In Volts:

28.0 dc

End Application:

Receiver set, infrared warning an/aar-44

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Nonpile-up Contact Arrangement:

2 pole, double throw, double break/double make, permanent jumper, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 0.500 amperes inductive dc

Special Features:

Horizontal split lens

Precious Material And Location:

Contacts gold

Terminal Type And Quantity:

13 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0