# NSN 5930-01-299-1352

Push Switch - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5930-01-299-1352

#### **Body Style:**

Panel mounted

#### Hazardous Locations/environmental Protection:

Explosion proof and humidity resistant

#### **Overall Length:**

3.096 inches

#### **Overall Height:**

0.750 inches

#### **Overall Width:**

0.750 inches

#### **Body Width:**

0.750 inches

#### **Body Height:**

0.750 inches

#### **Case Material:**

Metal

## Actuator Length:

0.620 inches

## Actuator Style:

Rectangular

## Actuator Height:

0.100 inches

#### Actuator Width:

0.620 inches

#### Actuator Color:

White single actuator and white single actuator

#### **Illuminated Actuator Color:**

Yellow single actuator and yellow single actuator

#### **Actuator Inscription:**

Enbld/on 1 single actuator

#### Maximum Voltage Rating In Volts:

28.0 dc

## Mounting Surface To Terminal End Distance:

2.756 inches

## Inclosure Type:

Fully enclosed

## Mounting Method:

Panel

## Features Provided:

Horizontal split lens

## Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

# NSN 5930-01-299-1352

Push Switch - Page 2 of 2



## Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 0.500 amperes inductive dc

## Precious Material And Location:

Contacts gold

## Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

---

## Demilitarization:

No

#### Fiig:

A053a0