# NSN 5930-01-299-1359

Push Switch - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5930-01-299-1359

# **Body Style:**

Panel mounted

### Hazardous Locations/environmental Protection:

Explosion proof and humidity resistant

#### **Overall Length:**

3.096 inches

#### **Overall Height:**

0.750 inches

#### **Overall Width:**

0.750 inches

#### **Body Width:**

0.750 inches

#### **Body Height:**

0.750 inches

#### **Case Material:**

Metal

# Actuator Length:

0.620 inches

# Actuator Style:

Rectangular

# Actuator Height:

0.100 inches

### Actuator Width:

0.620 inches

### Actuator Color:

White single actuator and white single actuator

#### **Illuminated Actuator Color:**

Amber single actuator and green single actuator

#### **Actuator Inscription:**

Alert/ptt 3 single actuator

# Illuminated Actuator Color Sequence:

Upper half of actuator amber lower half of acutator green

# Maximum Voltage Rating In Volts:

28.0 dc

#### Mounting Surface To Terminal End Distance:

2.756 inches

Inclosure Type:

Fully enclosed

# **Mounting Method:**

Panel

# **Features Provided:**

Horizontal split lens

# NSN 5930-01-299-1359

Push Switch - Page 2 of 2



# Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

# Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 0.500 amperes inductive dc

**Precious Material And Location:** 

Contacts gold

Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0