

View Online at <https://aerobasegroup.com/nsn/5930-01-299-1981>

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

4.834 inches

Overall Height:

5.060 inches

Overall Width:

2.340 inches

Body Height:

2.500 inches

Unthreaded Mounting Hole Diameter:

0.312 inches

Longest Horizontal Distance Between Mounting Centers:

4.210 inches

Longest Vertical Distance Between Mounting Centers:

1.870 inches

Pressure Switch Type:

Gage

Mounting Method:

Flange and unthreaded hole

Features Provided:

Electrical access port

Contact Action Stimulus:

Increase

Proof Pressure:

25.00 pounds per square inch

Mounting Facility Pattern:

Two position diagonal

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Tab w/screw

Contact Load Current Rating:

15.0 amperes resistive load second voltage

Contact Adjustability:

Actuation point adjustable, preset

Contact Adjustment Range:

+14.73/+20.00 actuation point pounds per square inch

Contact Adjustment Type:

Internal actuation point hex nut

Contact Stimulus Rating:

5.00 actuation point pounds per square inch

Contact Voltage Rating In Volts:

250.0 ac at sea level second voltage

Media For Which Designed:

Gas

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A048b0