NSN 5930-01-299-1990

Push Switch - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5930-01-299-1990

Body Style:

Panel mounted

Hazardous Locations/environmental Protection:

Explosion proof and humidity resistant

Overall Length:

3.096 inches

Overall Height:

0.750 inches

Overall Width:

0.750 inches

Body Width:

0.750 inches

Body Height:

0.750 inches

Case Material:

Metal

Actuator Length:

0.620 inches

Actuator Style:

Rectangular

Actuator Height:

0.100 inches

Actuator Width:

0.620 inches

Actuator Color:

White single actuator and white single actuator

Illuminated Actuator Color:

Amber single actuator and green single actuator

Actuator Inscription:

Alert/ptt 2 single actuator

Illuminated Actuator Color Sequence:

Upper half of actuator amber lower half of actuator green

Maximum Voltage Rating In Volts:

28.0 dc

Mounting Surface To Terminal End Distance:

2.756 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Features Provided:

Horizontal split lens

NSN 5930-01-299-1990

Push Switch - Page 2 of 2



Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 0.500 amperes inductive dc

Precious Material And Location:

Contacts gold

Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0