## NSN 5930-01-299-5568

Push-pull Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-299-5568

View Online at https://aerobasegroup.com/nsn/5930-01-299-5568
Body Style:
Panel mount
Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
1.375 inches
Overall Height:
0.875 inches
Overall Width:
0.875 inches
Body Diameter:
0.562 inches
Case Material:
Metal
Actuator Style:
Round
Actuator Diameter:
Between 0.355 inches and 0.395 inches
Actuator Height:
Between 0.235 inches and 0.265 inches
Actuator Color:
White single actuator
Maximum Voltage Rating In Volts:
5.0 dc
End Application:
Sonar set an/sqs 56
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Nonpile-up Contact Arrangement:
1 two circuit, double break/double make, both positions maintained single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
10.000 milliamperes resistive dc
Test Data Document:
81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
4 tab, solder lug
Specification Data:
96906-ms25089 government standard

N/a

Shelf Life:

## NSN 5930-01-299-5568

Push-pull Switch - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A053a0

Mil-std (military Standard):

Mil-s-8805 spec.