NSN 5930-01-299-6314

Flow Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-299-6314

Hazardous Locations/environmental Protection:
Corrosion resistant
Overall Length:
3.281 inches
Overall Width:
1.781 inches
Operating Tempurature Rating:
250.0 degrees fahrenheit
Mounting Method:
Line and threaded bushing
Features Provided:
Hermetically sealed case
Contact Action Stimulus:
Decrease
Thread Size:
0.500 inches single threaded bushing
Nonpile-up Contact Arrangement:
1 pole, single throw, normally closed, momentary action
Terminal Type:
Wire lead
Contact Load Current Rating:
500.0 milliamperes inductive load second voltage
Contact Adjustability:
Deactuation point not adjustable
Contact Stimulus Rating:
1.50 deactuation point gallons per minute
Contact Voltage Rating In Volts:
32.0 dc at sea level second voltage
Media For Which Designed:
Liquid
Precious Material And Location:
Contact surfaces silver
Precious Material:
Silver
Thread Series Designator:
Npt single threaded bushing
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

NSN 5930-01-299-6314

Flow Switch - Page 2 of 2



Fiig:

A048b0