NSN 5930-01-300-0466

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-300-0466

Thread Class:

2b single mounting facility

Overall Length:

3.972 inches

Overall Height:

2.812 inches

Overall Width:

2.812 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

2.203 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

2.203 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Bracket single mounting facility and threaded hole single mounting facility

Features Provided:

Actuator knob

Thread Size:

0.190 inches single mounting facility

Contact Voltage Rating In Volts:

600.0 highest ac voltage rating at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

2 single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes single section periphery

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

10.0 amperes inductive load lowest ac voltage rating at sea level

Precious Material And Location:

Contact surfaces silver

Precious Material:

Silver

NSN 5930-01-300-0466

Rotary Switch - Page 2 of 2



Style	De	sia	nato	r:
	-	v.9		

Tap, circuit selector

Thread Series Designator:

Unf single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0