NSN 5930-01-300-1547

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-300-1547

Thread Class:

2a single mounting facility

Thread Length:

0.230 inches single mounting facility and 0.255 inches single mounting facility

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

1.358 inches

First Flat Length:

0.235 inches single actuator and 0.265 inches single actuator

Flat Height:

0.093 inches single actuator

Shaft Diameter:

0.123 inches single actuator and 0.126 inches single actuator

Shaft Length:

0.375 inches single actuator

Overall Diameter:

0.500 inches

Individual Section Quantity:

· · ·

Nonturn Device Type:

Flatted bushing at 3: 00 o'clock

Operating Tempurature Range:

-65.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section rear

Throw Quantity:

10 single section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.250 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

10 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

NSN 5930-01-300-1547

Rotary Switch - Page 2 of 2



| Contact Switching Action: |
|---|
| Breaks before makes single section rear |
| Switch Actuator Positioning Increment: |
| 36.0 degrees single actuator |
| Detent Rotational Torque Range: |
| +0.500/+1.500 inch-pounds single actuator |
| Contact Load Current Rating: |
| 200.0 milliamperes resistive load dc at sea level and 30.0 milliamperes inductive load dc at sea level |
| Style Designator: |
| Snap or line |
| Test Data Document: |
| 81349-mil-s-3786 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Thread Series Designator: |
| Unf single mounting facility |
| Specification Data: |
| 81349-mil-s-3786/20 government specification |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

Demilitarization:

No

Fiig:

A052b0