

View Online at <https://aerobasegroup.com/nsn/5930-01-300-1816>

**Thread Class:**

2b all threaded hole

**Hazardous Locations/environmental Protection:**

Vibration resistant

**Overall Length:**

Between 4.594 inches and 4.968 inches

**Body Diameter:**

Between 0.618 inches and 0.625 inches

**Body Length:**

Between 3.562 inches and 3.624 inches

**Overall Diameter:**

1.750 inches

**Longest Horizontal Distance Between Mounting Centers:**

1.082 inches

**Shortest Horizontal Distance Between Mounting Centers:**

0.540 inches

**Longest Vertical Distance Between Mounting Centers:**

0.937 inches

**Temperature Sensing Element Type:**

Expanding shell

**Mounting Method:**

Bracket and threaded hole

**Thready Qty Per Inch (tpi):**

32 all threaded hole

**Contact Action Stimulus:**

Increase

**Thread Size:**

0.164 inches all threaded hole

**Mounting Facility Pattern:**

Isosceles triangle

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, momentary action

**Terminal Type:**

Wire lead

**Contact Load Current Rating:**

10.0 amperes resistive load first voltage5.0 amperes resistive load second voltage2.0 amperes resistive load third voltage

**Contact Adjustability:**

Actuation point adjustable, preset

**Contact Adjustment Range:**

-100.00/+400.00 actuation point degrees fahrenheit

**Contact Adjustment Type:**

External actuation point screw

**Contact Stimulus Rating:**

40.00 actuation point degrees fahrenheit

**Contact Voltage Rating In Volts:**

120.0 ac at sea level first voltage240.0 ac at sea level second voltage115.0 dc at sea level third voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Cylindrical w/flange

**Thread Series Designator:**

Unc all threaded hole

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0