NSN 5930-01-300-4943

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-300-4943

Inside Diameter:
0.250 inches single connection
Overall Length:
5.360 inches
Overall Height:
2.230 inches
Overall Width:
4.220 inches
Body Length:
3.000 inches
Unthreaded Mounting Hole Diameter:
0.250 inches
Distance Between Mounting Facility Centers:
2.750 inches
Pressure Switch Type:
Gage
Mounting Method:
Flange and unthreaded hole
Features Provided:
Electrical access port
Contact Action Stimulus:
Increase
Proof Pressure:
2500.00 pounds per square inch
Thread Size:
0.250 inches single pressure connection
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Screw
Contact Load Current Rating:
500.0 milliamperes resistive load second voltage
Contact Adjustability:
Actuation point adjustable and deactuation point adjustable
Contact Adjustment Range:
+20.00/+180.00 actuation point pounds per square inch and +20.00/+180.00 deactuation point pounds per square inch
Contact Adjustment Type:

Contact Voltage Rating In Volts:

Internal actuation point hex nut and internal deactuation point hex nut

480.0 ac at sea level first voltage

NSN 5930-01-300-4943

Pressure Switch - Page 2 of 2



Pressure Connector Type:
Plain, threaded internal single connection
Media For Which Designed:
Liquid
Style Designator:
Rectangular
Thread Series Designator:
Nptf single pressure connection
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A048b0