## NSN 5930-01-300-4946

Toggle Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-300-4946

| Body Style:  |
|--|
| Panel mount  |
| Hazardous Locations/environmental Protection:                                    |
| Dustproof  |
| Overall Length:  |
| 0.765 inches   |
| Overall Height:  |
| 1.421 inches   |
| Overall Width:   |
| 0.615 inches   |
| Body Length:   |
| 0.500 inches   |
| Body Width:  |
| 0.450 inches   |
| Body Height:   |
| 0.440 inches   |
| Case Material:   |
| Plastic  |
| Actuator Style:  |
| Rectangular  |
| Actuator Height:   |
| 0.456 inches   |
| Actuator Width:  |
| 0.450 inches   |
| Actuator Position-action Relationship:   |
| Up position momentary and down position momentary and center position maintained |
| Maximum Voltage Rating In Volts:   |
| 250.0 ac and 28.0 dc   |
| Inclosure Type:  |
| Fully enclosed   |
| Mounting Method:   |
| Panel  |
| Nonpile-up Contact Arrangement:  |
| 2 pole, double throw, two positions momentary single switch unit                 |
| Contact Load Current Rating At Maximum Rated Voltage:                            |
| 5.000 amperes resistive dc and 2.000 amperes resistive ac                        |
| Precious Material And Location:  |
| Terminal surfaces and contacts silver  |
| Terminal Type And Quantity:  |
| 6 tab, solder lug  |
| Shelf Life:  |

N/a

## **NSN 5930-01-300-4946** Toggle Switch - Page 2 of 2



| ı | In | it I | Of | · M | دما | e i | ıre: |
|---|----|------|----|-----|-----|-----|------|
| ι | JΝ | II ' | ωı | IV  | еа  | SU  | ıre: |

Demilitarization:

No

Fiig:

A053a0