NSN 5930-01-300-6819

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-300-6819

| Thread Class: |
|---|
| 2a |
| Body Style: |
| Bushing mounted |
| Overall Length: |
| 0.935 inches |
| Body Diameter: |
| 0.300 inches |
| Bushing Length: |
| 0.250 inches |
| Body Length: |
| 0.315 inches |
| Overall Diameter: |
| 0.375 inches |
| Actuator Style: |
| Round |
| Actuator Diameter: |
| 0.157 inches |
| Actuator Height: |
| 0.150 inches |
| Actuator Color: |
| Black single actuator |
| Maximum Voltage Rating In Volts: |
| 28.0 dc and 120.0 ac |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Threaded bushing |
| Thready Qty Per Inch (tpi): |
| 40 |
| Thread Size: |
| 0.250 inches |
| Nonpile-up Contact Arrangement: |
| 2 pole, single throw, normally open, double make, momentary action single switch unit |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 1.000 amperes resistive dc and 1.000 amperes resistive ac |
| Precious Material And Location: |
| Contact and terminal surfaces silver |
| Thread Series Designator: |
| Uns |
| Terminal Type And Quantity: |
| 4 tab, solder lug |

NSN 5930-01-300-6819

Push Switch - Page 2 of 2



| _ | | | • | | |
|---|---|----|---|----|----|
| • | n | ο. | • | 18 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0