

View Online at <https://aerobasegroup.com/nsn/5930-01-300-7739>

Hazardous Locations/environmental Protection:

Vibration resistant

Overall Length:

116.0 millimeters

Overall Width:

68.0 millimeters

Body Height:

79.0 millimeters

Unthreaded Mounting Hole Diameter:

7.0 millimeters

Longest Horizontal Distance Between Mounting Centers:

68.0 millimeters

Longest Vertical Distance Between Mounting Centers:

103.0 millimeters

Pressure Switch Type:

Gage

Mounting Method:

Bracket and slot and unthreaded hole

Features Provided:

Electrical access port

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

6.0 amperes inductive load single voltage

Contact Adjustability:

Actuation point not adjustable

Contact Stimulus Rating:

0.00 actuation point bar and 8.00 actuation point bar

Contact Voltage Rating In Volts:

440.0 ac at sea level single voltage

Media For Which Designed:

Liquid

Precious Material And Location:

Contact surfaces gold and contacts silver

Precious Material:

Gold and silver

Style Designator:

Rectangular w/bracket

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0