

View Online at <https://aerobasegroup.com/nsn/5930-01-300-7739>

**Hazardous Locations/environmental Protection:**

Vibration resistant

**Overall Length:**

116.0 millimeters

**Overall Width:**

68.0 millimeters

**Body Height:**

79.0 millimeters

**Unthreaded Mounting Hole Diameter:**

7.0 millimeters

**Longest Horizontal Distance Between Mounting Centers:**

68.0 millimeters

**Longest Vertical Distance Between Mounting Centers:**

103.0 millimeters

**Pressure Switch Type:**

Gage

**Mounting Method:**

Bracket and slot and unthreaded hole

**Features Provided:**

Electrical access port

**Contact Action Stimulus:**

Increase

**Mounting Facility Pattern:**

Four position rectangular

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Screw

**Contact Load Current Rating:**

6.0 amperes inductive load single voltage

**Contact Adjustability:**

Actuation point not adjustable

**Contact Stimulus Rating:**

0.00 actuation point bar and 8.00 actuation point bar

**Contact Voltage Rating In Volts:**

440.0 ac at sea level single voltage

**Media For Which Designed:**

Liquid

**Precious Material And Location:**

Contact surfaces gold and contacts silver

**Precious Material:**

Gold and silver

**Style Designator:**

Rectangular w/bracket

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0