

View Online at <https://aerobasegroup.com/nsn/5930-01-300-7742>

Inside Diameter:

0.250 inches single connection

Hazardous Locations/environmental Protection:

Weathertight

Overall Length:

4.220 inches

Overall Height:

5.360 inches

Overall Width:

2.230 inches

Body Height:

3.000 inches

Unthreaded Mounting Hole Diameter:

0.281 inches

Distance Between Mounting Facility Centers:

2.750 inches

Pressure Switch Type:

Gage

Mounting Method:

Flange and unthreaded hole

Features Provided:

Electrical access port

Contact Action Stimulus:

Increase

Proof Pressure:

2500.00 pounds per square inch

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Tab w/screw

Contact Load Current Rating:

0.4 amperes resistive load second voltage

Contact Adjustability:

Actuation point adjustable

Contact Adjustment Range:

+20.00/+180.00 actuation point pounds per square inch

Contact Adjustment Type:

Internal actuation point hex nut

Contact Voltage Rating In Volts:

480.0 ac at sea level first voltage

Pressure Connector Type:

Swivel nut, gasket seal, threaded internal single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Thread Series Designator:

Nptf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0