NSN 5930-01-300-7748

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-300-7748

Hazardous Locations/environmental Protection:
Watertight and oiltight
Overall Length:
7.062 inches
Overall Height:
3.188 inches
Overall Width:
2.281 inches
Housing Height:
2.500 inches
Housing Length:
6.250 inches
Housing Width:
2.281 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
2.625 inches
Maximum Voltage Rating In Volts:
600.0 ac and 250.0 dc
Inclosure Type:
Fully enclosed
Thready Qty Per Inch (tpi):
20
Thread Size:
0.250 inches
Nonpile-up Contact Arrangement:
2 two circuit, double break/double make, one position momentary single switch unit
Actuator Movement:
18.0 pretravel degrees and 72.0 overtravel degrees and 14.0 differential degrees
Contact Load Current Rating At Maximum Rated Voltage:
1.500 amperes resistive dc and 5.000 amperes resistive ac
Special Features:
Less operating lever
Precious Material And Location:
Contacts silver
Thread Series Designator:
Unc
Terminal Type And Quantity:
8 screw
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5930-01-300-7748

Sensitive Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A053a0