Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-300-7748

Hazardous Locations/environmental Protection:

Watertight and oiltight

Overall Length:

7.062 inches

Overall Height:

3.188 inches

Overall Width:

2.281 inches

Housing Height:

2.500 inches

Housing Length:

6.250 inches

Housing Width:

2.281 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

2.625 inches

Maximum Voltage Rating In Volts:

600.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Thready Qty Per Inch (tpi):

20

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

2 two circuit, double break/double make, one position momentary single switch unit

Actuator Movement:

18.0 pretravel degrees and 72.0 overtravel degrees and 14.0 differential degrees

Contact Load Current Rating At Maximum Rated Voltage:

1.500 amperes resistive dc and 5.000 amperes resistive ac

Special Features:

Less operating lever

Precious Material And Location:

Contacts silver

Thread Series Designator:

Unc

Terminal Type And Quantity:

8 screw

Shelf Life:

N/a

Unit Of Measure:

NSN 5930-01-300-7748

Sensitive Switch - Page 2 of 2

Demilitarization:

No

Fiig:

A053a0

