NSN 5930-01-300-7755

Hazardous Locations/environmental Protection:

Push Switch - Page 1 of 2

Body Style:

Waterproof

Bushing mounted

Overall Length: 2.220 inches Overall Height:



View Online at https://aerobasegroup.com/nsn/5930-01-300-7755

0.750 inches
Overall Width:
0.750 inches
Body Diameter:
0.562 inches
Bushing Length:
Between 0.415 inches and 0.435 inches
Body Length:
Between 1.200 inches and 1.260 inches
Case Material:
Metal
Actuator Length:
0.750 inches
Actuator Style:
Rectangular
Actuator Height:
0.440 inches
Actuator Width:
0.750 inches
Actuator Color:
Black single actuator
Illuminated Actuator Color:
Black single actuator
Actuator Inscription:
1 single actuator
Maximum Voltage Rating In Volts:
28.0 dc
End Application:
Sonar set an/sqs-56
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded bushing
Features Provided:
Actuator seal

NSN 5930-01-300-7755Push Switch - Page 2 of 2



Thready Qty Per Inch (tpi):
32
Thread Size:
0.468 inches
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
1.000 amperes resistive dc and 0.500 amperes inductive dc
Special Features:
Illuminated actuator inscription characters are red
Precious Material And Location:
Contacts gold
Thread Series Designator:
Uns
Terminal Type And Quantity:
3 turret and 2 tab, solder lug
Specification Data:
49956-853213 manufacturers source control
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A053a0