# NSN 5930-01-300-7757

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-300-7757

# Body Style:

Bushing mounted

# Hazardous Locations/environmental Protection:

Waterproof

# **Overall Length:**

2.220 inches

#### **Overall Height:**

0.750 inches

#### **Overall Width:**

0.750 inches

## **Body Diameter:**

0.562 inches

#### Bushing Length:

Between 0.415 inches and 0.435 inches

#### **Body Length:**

Between 1.200 inches and 1.260 inches

#### **Case Material:**

Metal

#### Actuator Length:

0.750 inches

#### **Actuator Style:**

Rectangular

#### Actuator Height:

0.440 inches

# Actuator Width:

0.750 inches

#### Actuator Color:

Black single actuator

#### Illuminated Actuator Color:

Black single actuator

#### **Actuator Inscription:**

Enter data single actuator

#### Maximum Voltage Rating In Volts:

28.0 dc

#### **End Application:**

Sonar set an/sqs-56

#### Inclosure Type:

Fully enclosed

#### **Mounting Method:**

Threaded bushing

## **Features Provided:**

Actuator seal

# **NSN 5930-01-300-7757** Push Switch - Page 2 of 2



Thready Qty Per Inch (tpi):
32
Thread Size:
0.468 inches
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
1.000 amperes resistive dc and 0.500 amperes inductive dc
Special Features:
Illuminated actuator inscription characters are red
Precious Material And Location:
Contacts gold
Thread Series Designator:
Uns
Terminal Type And Quantity:
3 turret and 2 tab, solder lug
Specification Data:
49956-853213 manufacturers source control
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig:

A053a0