## NSN 5930-01-300-7758

Push Switch - Page 1 of 2



- asir emissi i age i si z	ui
View Online at https://aerobasegroup.com/nsn/5930-01-300-7758	
Body Style:	
Bushing mounted	
Hazardous Locations/environmental Protection:	
Waterproof	
Overall Length:	
2.220 inches	
Overall Height:	
0.750 inches	
Overall Width:	
0.750 inches	
Body Diameter:	
0.562 inches	
Bushing Length:	
Between 0.415 inches and 0.435 inches	
Body Length:	
Between 1.200 inches and 1.260 inches	
Case Material:	
Metal	
Actuator Length:	
0.750 inches	
Actuator Style:	
Rectangular	
Actuator Height:	
0.440 inches	
Actuator Width:	
0.750 inches	
Actuator Color:	
Black single actuator	
Illuminated Actuator Color:	
Black single actuator	
Actuator Inscription:	
Next mode single actuator	
Maximum Voltage Rating In Volts:	
28.0 dc	
End Application:	

Sonar set an/sqs-56

Inclosure Type:

Fully enclosed

**Mounting Method:** 

Threaded bushing

**Features Provided:** 

Actuator seal

## **NSN 5930-01-300-7758**Push Switch - Page 2 of 2



Thready Qty Per Inch (tpi):
32
Thread Size:
0.468 inches
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
1.000 amperes resistive dc and 0.500 amperes inductive dc
Special Features:
Illuminated actuator inscription characters are red
Precious Material And Location:
Contacts gold
Thread Series Designator:
Uns
Terminal Type And Quantity:
3 turret and 2 tab, solder lug
Specification Data:
49956-853213 manufacturers source control
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A053a0