NSN 5930-01-300-8285

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-300-8285

| Body Style: | | | | |
|---|--|--|--|--|
| Panel mounted | | | | |
| Overall Length: | | | | |
| 1.780 inches | | | | |
| Overall Height: | | | | |
| 0.437 inches | | | | |
| Overall Width: | | | | |
| 0.688 inches | | | | |
| Body Width: | | | | |
| 0.688 inches | | | | |
| Body Height: | | | | |
| 0.437 inches | | | | |
| Case Material: | | | | |
| Metal | | | | |
| Actuator Length: | | | | |
| 0.640 inches | | | | |
| Actuator Style: | | | | |
| Rectangular | | | | |
| Actuator Height: | | | | |
| 0.110 inches | | | | |
| Actuator Width: | | | | |
| 0.390 inches | | | | |
| Actuator Color: | | | | |
| Black single actuator | | | | |
| Illuminated Actuator Color: | | | | |
| Green single actuator | | | | |
| Actuator Inscription: | | | | |
| Fail single actuator | | | | |
| Maximum Voltage Rating In Volts: | | | | |
| 28.0 dc | | | | |
| Mounting Surface To Terminal End Distance: | | | | |
| 1.670 inches | | | | |
| Inclosure Type: | | | | |
| Fully enclosed | | | | |
| Mounting Method: | | | | |
| Panel | | | | |
| Features Provided: | | | | |
| Full display lens | | | | |
| Nonpile-up Contact Arrangement: | | | | |
| 1 pole, double throw, one position momentary single switch unit | | | | |

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 0.500 amperes inductive dc

NSN 5930-01-300-8285

Push Switch - Page 2 of 2



| Precious | Material | ∆nd ∣ | Location: |
|----------|------------|--------|------------|
| riccious | iviale lai | Allu I | LUCALIUII. |

Contacts gold

Terminal Type And Quantity:

3 tab, solder lug and 3 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0