

View Online at <https://aerobasegroup.com/nsn/5930-01-300-9793>

Thread Class:

2b single mounting facility

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

2.400 inches

First Flat Length:

0.490 inches single actuator and 0.510 inches single actuator

Flat Height:

0.177 inches single actuator and 0.197 inches single actuator

Shaft Diameter:

0.240 inches single actuator and 0.260 inches single actuator

Shaft Length:

0.772 inches single actuator

Overall Diameter:

1.960 inches

Distance Between Mounting Facility Centers:

1.584 inches single mounting facility and 1.604 inches single mounting facility

Individual Section Quantity:

1

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section periphery

Throw Quantity:

7 single section periphery

Mounting Method:

Threaded hole single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.138 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Mounting Facility Pattern:

Two position in-line single mounting facility

Switch Actuator Indexing Position Quantity:

8 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes single section periphery

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Contact Load Current Rating:

10.0 amperes resistive load dc at sea level

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0