NSN 5930-01-301-0056



Toggle Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-01-301-0056 **Thread Class:** 2a **Body Style: Bushing mount Hazardous Locations/environmental Protection:** Splashproof **Overall Length:** 0.500 inches **Overall Height:** 1.269 inches **Overall Width:** 0.270 inches **Bushing Length:** 0.294 inches **Body Length:** 0.500 inches **Body Width:** 0.270 inches **Body Height:** 0.350 inches **Case Material:** Plastic **Actuator Style:** Round **Actuator Diameter:** 0.105 inches **Actuator Height:** 0.200 inches **Actuator Position-action Relationship:** Up position maintained and down position maintained **Maximum Voltage Rating In Volts:** 28.0 dc and 250.0 ac **Inclosure Type:** Fully enclosed **Mounting Method:** Threaded bushing Thready Qty Per Inch (tpi): 40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

NSN 5930-01-301-0056

Toggle Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.000 amperes resistive ac

Precious Material And Location:

Contact and terminal surfaces gold

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 wire wrap

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0