

View Online at <https://aerobasegroup.com/nsn/5930-01-301-4735>

**Hazardous Locations/environmental Protection:**

Vibration resistant

**Overall Length:**

4.405 inches

**Body Diameter:**

Between 0.618 inches and 0.625 inches

**Body Length:**

Between 3.656 inches and 3.780 inches

**Overall Diameter:**

0.656 inches

**Temperature Sensing Element Type:**

Expanding shell

**Operating Temperature Rating:**

Between -100.0 degrees fahrenheit and 225.0 degrees fahrenheit

**Mounting Method:**

Clamp

**Contact Action Stimulus:**

Increase

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally closed, momentary action

**Terminal Type:**

Wire lead

**Contact Load Current Rating:**

10.0 amperes resistive load first voltage5.0 amperes resistive load second voltage2.0 amperes resistive load third voltage

**Contact Adjustability:**

Actuation point adjustable, preset

**Contact Adjustment Range:**

-100.00/+600.00 actuation point degrees fahrenheit

**Contact Adjustment Type:**

External actuation point screw

**Contact Stimulus Rating:**

125.00 actuation point degrees fahrenheit

**Contact Voltage Rating In Volts:**

120.0 ac at sea level first voltage240.0 ac at sea level second voltage115.0 dc at sea level third voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Cylindrical

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0