

View Online at <https://aerobasegroup.com/nsn/5930-01-301-4817>

Body Style:

Panel mount

Hazardous Locations/environmental Protection:

Shock resistant and vibration resistant

Overall Length:

Between 0.802 inches and 0.822 inches

Overall Height:

3.221 inches

Overall Width:

Between 0.802 inches and 0.822 inches

Body Length:

0.688 inches

Body Width:

0.688 inches

Body Height:

2.761 inches

Case Material:

Metal

Actuator Length:

Between 0.802 inches and 0.822 inches

Actuator Style:

Rectangular

Actuator Height:

Between 0.400 inches and 0.460 inches

Actuator Width:

Between 0.802 inches and 0.822 inches

Actuator Color:

Black single actuator and black single actuator and black single actuator

Illuminated Actuator Color:

Black single actuator and black single actuator and black single actuator

Actuator Inscription:

Lh cheek blowers/no.1/no.2 single actuator

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 0.500 amperes inductive dc

Special Features:

Illuminated actuator inscription characters are green; three-way split lens

Precious Material And Location:

Contacts gold

Terminal Type And Quantity:

6 turret and 5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0