

View Online at <https://aerobasegroup.com/nsn/5930-01-301-4817>

**Body Style:**

Panel mount

**Hazardous Locations/environmental Protection:**

Shock resistant and vibration resistant

**Overall Length:**

Between 0.802 inches and 0.822 inches

**Overall Height:**

3.221 inches

**Overall Width:**

Between 0.802 inches and 0.822 inches

**Body Length:**

0.688 inches

**Body Width:**

0.688 inches

**Body Height:**

2.761 inches

**Case Material:**

Metal

**Actuator Length:**

Between 0.802 inches and 0.822 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

Between 0.400 inches and 0.460 inches

**Actuator Width:**

Between 0.802 inches and 0.822 inches

**Actuator Color:**

Black single actuator and black single actuator and black single actuator

**Illuminated Actuator Color:**

Black single actuator and black single actuator and black single actuator

**Actuator Inscription:**

Lh cheek blowers/no.1/no.2 single actuator

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Nonpile-up Contact Arrangement:**

2 pole, double throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

1.000 amperes resistive dc and 0.500 amperes inductive dc

**Special Features:**

Illuminated actuator inscription characters are green; three-way split lens

**Precious Material And Location:**

Contacts gold

**Terminal Type And Quantity:**

6 turret and 5 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0