NSN 5930-01-301-6802

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-301-6802

view Online at https://aerobasegroup.com/nsn/5950-01-501-6802
Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
3.080 inches
Overall Height:
1.772 inches
Overall Width:
1.693 inches
ndividual Section Quantity:
1
Knob Manufacturer Code:
37833
Knob Manufacturer Part Number:
Zb2-bd2
Operating Tempurature Range:
20.0/+70.0 degrees celsius
Switch Contact Basic Design:
Nonpile-up nonsymmetrical
Mounting Method:
Bracket single mounting facility
Features Provided:
Actuator knob
Contact Voltage Rating In Volts:
600.0 highest ac voltage rating at sea level120.0 lowest ac voltage rating at sea level600.0 highest dc voltage rating at sea level120.0 lowest
dc voltage rating at sea level
Switch Actuator Indexing Position Quantity:
2 single actuator
Terminal Type:
Screw
Switch Actuator Positioning Increment:
90.0 degrees single actuator
Switch Actuator Stop Device Type:
Fixed stop single actuator
Contact Load Current Rating:
1.2 amperes resistive load highest ac voltage rating at sea level6.0 amperes resistive load lowest ac voltage rating at sea level200.0
milliamperes resistive load highest dc voltage rating at sea level1.1 amperes resistive load lowest dc voltage rating at sea level
Precious Material And Location:
Contact surfaces silver
Precious Material:
Silver
Style Designator:
Cap. circuit selector

N/a

Shelf Life:

NSN 5930-01-301-6802 Rotary Switch - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

Demilitarization:

No

Fiig:

A052b0