

View Online at <https://aerobasegroup.com/nsn/5930-01-301-6939>

Thread Class:

2a

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Moisture resistant and salt spray resistant and shock resistant and vibration resistant

Overall Length:

Between 1.594 inches and 1.718 inches

Overall Height:

0.875 inches

Overall Width:

0.875 inches

Bushing Length:

Between 0.714 inches and 0.766 inches

Body Length:

0.609 inches

Case Material:

Metal

Actuator Diameter:

0.875 inches

Actuator Height:

0.219 inches

Actuator Color:

Red single actuator

Maximum Voltage Rating In Volts:

120.0 ac and 28.0 dc

End Application:

5895-01-269-3572 landing control central

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

24

Thread Size:

0.625 inches

Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 5.000 amperes inductive dc and 3.000 amperes lamp dc and 10.000 amperes resistive ac and 5.000 amperes inductive ac and 3.000 amperes lamp ac

Thread Series Designator:

Unef

Terminal Type And Quantity:

4 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0