

View Online at <https://aerobasegroup.com/nsn/5930-01-301-9799>

Body Style:

Panel mount

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

0.750 inches

Overall Height:

4.814 inches

Overall Width:

0.750 inches

Body Length:

0.750 inches

Body Width:

0.750 inches

Body Height:

3.535 inches

Case Material:

Metal

Actuator Length:

0.625 inches

Actuator Style:

Rectangular

Actuator Height:

0.120 inches

Actuator Width:

0.625 inches

Actuator Color:

Black single actuator and black single actuator

Illuminated Actuator Color:

Black single actuator and black single actuator

Actuator Inscription:

Low single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Nonpile-up Contact Arrangement:

3 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 7.500 amperes resistive ac and 5.000 amperes inductive ac and 1.000 amperes lamp ac

Special Features:

Vertical split lens; dim/test control module provided; 0.125 in. W strip of 0.020 diameter dot on a 36 line density pattern on right side of actuator

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0