

View Online at <https://aerobasegroup.com/nsn/5930-01-302-0802>

Thread Class:

2a

Body Style:

Bushing mounted

Overall Length:

3.205 inches

Overall Width:

Between 1.485 inches and 1.515 inches

Body Diameter:

Between 1.485 inches and 1.515 inches

Bushing Length:

Between 0.970 inches and 1.030 inches

Body Length:

1.700 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.563 inches and 0.573 inches

Actuator Height:

Between 0.465 inches and 0.485 inches

Actuator Free Position Height:

Between 1.445 inches and 1.505 inches

Maximum Voltage Rating In Volts:

115.0 ac and 115.0 dc

End Application:

Helicopter uh-1n

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thread Size:

0.625 inches

Nonpile-up Contact Arrangement:

2 two circuit, double break/double make, one position momentary single switch unit

Switch Release Force:

32.0 ounces

Criticality Code Justification:

Feat

Switch Actuating Force:

Between 48.0 ounces and 128.0 ounces

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 0.500 amperes inductive dc and 10.000 amperes resistive ac and 10.000 amperes inductive ac

Special Features:

Weapon system essential

Thread Series Designator:

Unef

Terminal Type And Quantity:

8 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0