

View Online at <https://aerobasegroup.com/nsn/5930-01-302-3308>

**Body Style:**

Bushing mount

**Bushing Length:**

0.300 inches

**Body Length:**

0.510 inches

**Body Width:**

0.465 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.115 inches

**Actuator Height:**

0.410 inches

**Actuator Position-action Relationship:**

Up position momentary and down position momentary and center position maintained

**Maximum Voltage Rating In Volts:**

28.0 ac and 28.0 dc

**Mounting Surface To Terminal End Distance:**

0.577 inches

**Inclosure Type:**

Fully enclosed

**Features Provided:**

Actuator seal

**Thready Qty Per Inch (tpi):**

40

**Thread Size:**

0.250 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, two positions momentary single switch unit

**Precious Material And Location:**

Terminal surface option gold or terminal surface option silver

**Test Data Document:**

81349-mil-s-83731 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

6 tab, solder lug

**Specification Data:**

81349-mil-s-83731/10 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0