## NSN 5930-01-302-4333

Sensitive Switch - Page 1 of 2

---



View Online at https://aerobasegroup.com/nsn/5930-01-302-4333

De de Otoles
Body Style:
Hole mounted
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.875 inches
Body Length:
1.090 inches
Body Width:
0.400 inches
Body Height:
0.760 inches
Unthreaded Mounting Hole Diameter:
0.114 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.406 inches
Actuator Style:
Roller arm
Actuator Free Position Height:
0.810 inches
Actuator Roller Diameter:
0.190 inches
Actuator Roller Width:
0.190 inches
Maximum Voltage Rating In Volts:
250.0 ac and 250.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Actuating Force:
15.0 grams
Actuator Movement:
0.056 pretravel inches and 0.040 overtravel inches and 0.013 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
250.000 milliamperes resistive dc and 15.000 amperes resistive ac
Terminal Type And Quantity:
3 quick disconnect, male
Shelf Life:
N/a
Unit Of Measure:

## NSN 5930-01-302-4333

Sensitive Switch - Page 2 of 2

Demilitarization:

No

Fiig:

A053a0

