# NSN 5930-01-302-4334

**Hazardous Locations/environmental Protection:** 

Push Switch - Page 1 of 2

Explosion proof and humidity resistant

**Body Style:**Panel mounted



View Online at https://aerobasegroup.com/nsn/5930-01-302-4334

Overall Length:
4.814 inches
Overall Height:
0.750 inches
Overall Width:
0.750 inches
Body Width:
0.750 inches
Body Height:
0.750 inches
Case Material:
Metal
Actuator Length:
0.625 inches
Actuator Style:
Rectangular
Actuator Height:
0.120 inches
Actuator Width:
0.625 inches
Actuator Color:
Black and black single actuator
Illuminated Actuator Color:
Black and black single actuator
Actuator Inscription:
Open close single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Mounting Surface To Terminal End Distance:
3.535 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Horizontal split lens
Nonpile-up Contact Arrangement:
$3 \ \mathrm{pole}, \ \mathrm{double} \ \mathrm{throw}, \ \mathrm{both} \ \mathrm{positions} \ \mathrm{maintained} \ \mathrm{single} \ \mathrm{switch} \ \mathrm{unit}$

## NSN 5930-01-302-4334

Push Switch - Page 2 of 2



## **Contact Load Current Rating At Maximum Rated Voltage:**

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 7.500 amperes resistive ac and 5.000 amperes inductive ac and 1.000 amperes lamp ac

### **Special Features:**

Dim/test control module provided; illuminated actuator inscription is green and amber

**Precious Material And Location:** 

Contacts silver

#### **Terminal Type And Quantity:**

1 socket, integrated wire termination

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0